SUPERFIN 200 AUS

Масло для металлообработки

SUPERFIN 200 AUS - охлаждающая жидкость на основе минерального масла, специально разработанная для операций микро обработки и заточки сплавов ALUSIL, чугуна и стали.

Благодаря большому количеству полярных присадок и низкой вязкости, продукт демонстрирует отличные смазывающие и оптимальные моющие свойства.

SUPERFIN 200 AUS обеспечивает отличную фильтруемость.

SUPERFIN 200 AUS не содержит соединений цинка и хлора, содержащиеся стабилизаторы окисления обеспечивают высокую стабильность в процессе эксплуатации.

Характеристики

Внешний вид		Прозрачный, светло желтый	
Плотность/20 °C	DIN 51757	приблиз. 0.842	г/см³
Вязкость/40 °C	DIN 51562/1	приблиз. 5.1	мм²/сек
Температура вспышки	DIN 51376	> 125	°C
Температура замерзания	ISO 3016	< - 3	°C
Тест коррозии меди	DIN EN ISO 2160	< 2 – 100 – A3	

Действует только в сочетании с паспортом безопасности ЕС **110531-fc-1216090**

The information given here is considered to be correct and is offered for your consideration, investigation and verification. No warranties are expressed or implied since the use of our products is beyond our control. Statements concerning the use of PETROFER products are not to be construed as recommending the infringement of any patent.

PETROFER CHEMIE, Römerring 12-16, D-31137 Hildesheim; Phone + 49 51 21 / 76 27-0, Fax + 49 51 21 / 5 44 38 Mail: info@petrofer.com, Web: http://www.petrofer.com